



NOTE GROUND SWITCH .047
125V.A.C. AND AC RECEPTACLE DELETED.

CAUTION:

500 VOLTS AVAILABLE. DISCONNECT POWER SUPPLY
AND ALLOW AT LEAST 20 SECONDS FOR VOLTAGES
TO BLEED OFF. BEFORE SERVICING AMPLIFIER.

- DENOTES TYPICAL 1KHz SIGNAL FOR 10W OUTPUT WITH CONTROLS AT MAX.
- △ USED IN SOME VERSIONS.
- 3. WHEN INSTALLING NEW 6L6'S RESET O.T. MATCHING FOR MIN. HUM.
- 2. ALL CAPACITORS AT LEAST 600 VOLT RATING IF NOT SPECIFIED.
- 1. ALL RESISTORS 1/2 WATT, 10% TOLERANCE IF NOT SPECIFIED.

NOTES: UNLESS OTHERWISE SPECIFIED

Fender/Rogers/Rhodes
OUR ORIGINAL INSTRUMENTS - A DIVISION OF GEA, INC.
 FULLERTON, CALIFORNIA 92631

PART NAME
SCHEMATIC
BASSMAN 70
 70 WATT RMS AMPLIFIER-DOMESTIC EXPORT

RELEASE	DATE	PART NO.	REV.
		014229	A