



CAUTION 500 VOLTS AVAILABLE. DISCONNECT POWER SUPPLY BEFORE SERVICING AND ALLOW 10 SECONDS FOR BLEEDERS TO DISSIPATE B+ VOLTAGES.

FENDER MUSICAL INSTRUMENTS
 CBS MUSICAL INSTRUMENTS
 A DIVISION OF CBS INC.
 FULLERTON CALIFORNIA
 U.S.A.

TEST DATA
 (BV) DENOTES TYPICAL 1KH₂ SIGNAL FOR 10 WATTS OUTPUT.
 INSERT PLUG INTO INPUT JACK .
 CONTROL SETTINGS- EQUALIZERS AT MID POSITION,
 DISTORTION AND PRESENCE AT MINIMUM.
 OTHERS AT MAXIMUM.
 2A-USE 0.1MFD 600V CAPACITOR IN SERIES WITH GENERATOR.
 D.C. VOLTAGES READ WITH NO SIGNAL INPUT AND DISTORTION OFF.

2 ALL RESISTORS ARE 1/2W, 10%.
 1. ALL CAPACITORS AT LEAST 500 V.D.C.
 NOTES: UNLESS OTHERWISE SPECIFIED

Fender/Rosen/Rhodes
 - SCHEMATIC -
 150 WATT GUITAR
 AMPLIFIER
 012380